



YES! WE ARE HONOR!

CNC VERTICAL LATHE CNC VERTICAL TURNING CENTER

High Speed Series : VL-46 ~ VL-100

Heavy Duty Series : VL-66 ~ VL-250



High precision
High efficiency
High durability
Perfection

CE



ISO 9001:2008



HONOR SEIKI Co., Ltd.

CNC Vertical Lathe/High Speed Series

VL-46A



Max. swing dia.: 560mm
Max. turning dia.: 460mm
Max. turning height: 450mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Turret: H12

VL-46AR



Max. swing dia.: 560mm
Max. turning dia.: 460mm
Max. turning height: 450mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Turret: H12

VL-46AT



Max. swing dia.: 560mm
Max. turning dia.: 460mm
Max. turning height: 450mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Turret: H12+H12

VL-46H



Max. swing dia.: 650mm
Max. turning dia.: 460mm
Max. turning height: 350mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Turret: V4/V6/V8

VL-46G



Max. swing dia.: 600mm
Max. turning dia.: 460mm
Max. turning height: 350mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Turret: G5

VL-66A



Max. swing dia.: 800mm
Max. turning dia.: 760mm
Max. turning height: 750mm
Chuck dia.: 18 inch
Spindle bearing dia.: 160mm
Spindle speed: 25-2000rpm
Turret: H12

VL-66AR



Max. swing dia.: 800mm
Max. turning dia.: 760mm
Max. turning height: 750mm
Chuck dia.: 18 inch
Spindle bearing dia.: 160mm
Spindle speed: 25-2000rpm
Turret: H12

VL-66AT



Max. swing dia.: 800mm
Max. turning dia.: 760mm
Max. turning height: 750mm
Chuck dia.: 18 inch
Spindle bearing dia.: 160mm
Spindle speed: 25-2000rpm
Turret: H12+H12

VL-66H



Max. swing dia.: 850mm
Max. turning dia.: 760mm
Max. turning height: 620mm
Chuck dia.: 18 inch
Spindle bearing dia.: 160mm
Spindle speed: 25-2000rpm
Turret: V4/V6/V8

VL-86A



Max. swing dia.: 1000mm
Max. turning dia.: 860mm
Max. turning height: 810mm
Chuck dia.: 21 inch
Spindle bearing dia.: 200mm
Spindle speed: 25-1500rpm
Turret: H12

VL-86AR



Max. swing dia.: 1000mm
Max. turning dia.: 860mm
Max. turning height: 810mm
Chuck dia.: 21 inch
Spindle bearing dia.: 200mm
Spindle speed: 25-1500rpm
Turret: H12

VL-86AT



Max. swing dia.: 1000mm
Max. turning dia.: 860mm
Max. turning height: 810mm
Chuck dia.: 21 inch
Spindle bearing dia.: 200mm
Spindle speed: 25-1500rpm
Turret: H12+H12

CNC Vertical Lathe/Heavy Duty Series

 VL-86H



Max. swing dia.: 1000mm
Max. turning dia.: 860mm
Max. turning height: 800mm
Chuck dia.: 21 inch
Spindle bearing dia.: 200mm
Spindle speed: 25-1500rpm
Turret: V4/V6/V8

 VL-66C



Max. swing dia.: 850mm
Max. turning dia.: 850mm
Max. turning height: 650mm
Chuck dia.: 21 inch
Spindle speed: 5-700rpm
ATC: 12 positions

 VL-86C



Max. swing dia.: 950mm
Max. turning dia.: 950mm
Max. turning height: 650mm
Chuck dia.: 24 inch
Spindle speed: 5-600rpm
ATC: 12 positions

 VL-100C



Max. swing dia.: 1200mm
Max. turning dia.: 1200mm
Max. turning height: 650(800)mm
Table dia.: 1000mm
Spindle speed: 3-400rpm
ATC: 12 positions

 VL-125C



Max. swing dia.: 1600mm
Max. turning dia.: 1600mm
Max. turning height: 1200mm
Table dia.: 1250mm
Spindle speed: 3-300rpm
ATC: 12/16 positions

 VL-160C



Max. swing dia.: 2000mm
Max. turning dia.: 2000mm
Max. turning height: 1200mm
Table dia.: 1600mm
Spindle speed: 3-250rpm
ATC: 12/16 positions

 VL-200C



Max. swing dia.: 2500mm
Max. turning dia.: 2500mm
Max. turning height: 1600mm
Table dia.: 2000mm
Spindle speed: 5-200rpm
ATC: 12/16 positions

 VL-250C



Max. swing dia.: 3000mm
Max. turning dia.: 2970mm
Max. turning height: 1600mm
Table dia.: 2500mm
Spindle speed: 5-160rpm
ATC: 12/16 positions

CNC Vertical Turning Center

 VL-46M



Max. swing dia.: 560mm
Max. turning dia.: 460mm
Max. turning height: 380mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Power turret: H12
C axis

 VL-66M



Max. swing dia.: 800mm
Max. turning dia.: 740mm
Max. turning height: 690mm
Chuck dia.: 18 inch
Spindle bearing dia.: 160mm
Spindle speed: 25-2000rpm
Power turret: H12
C axis

 VL-86M



Max. swing dia.: 1000mm
Max. turning dia.: 850mm
Max. turning height: 760mm
Chuck dia.: 21 inch
Spindle bearing dia.: 200mm
Spindle speed: 25-1500rpm
Power turret: H12
C axis

 VL-46MT



Max. swing dia.: 560mm
Max. turning dia.: 460mm
Max. turning height: 380mm
Chuck dia.: 12 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-2500rpm
Power turret: H12+H12
C axis

CNC Vertical Turning Center

VL-66MT



Max. swing dia.: 800mm
Max. turning dia.: 740mm
Max. turning height: 690mm
Chuck dia.: 18 inch
Spindle bearing dia.: 160mm
Spindle speed: 25-2000rpm
Power turret: H12+H12
C axis

VL-86MT



Max. swing dia.: 1000mm
Max. turning dia.: 850mm
Max. turning height: 760mm
Chuck dia.: 21 inch
Spindle bearing dia.: 200mm
Spindle speed: 25-1500rpm
Power turret: H12+H12
C axis

VL-66CM/86CM



Max. swing dia.: 950mm
Max. turning dia.: 900mm
Max. turning height: 650mm
Chuck dia.: 24 inch
Spindle speed: 5-600rpm
ATC: 12 positions
Live Tool Spindle
C axis

VL-100CM



Max. swing dia.: 1200mm
Max. turning dia.: 1100mm
Max. turning height: 650(800)mm
Table dia.: 1000mm
Spindle speed: 3-400rpm
ATC: 12 positions
Live Tool Spindle
C axis

VL-125CM



Max. swing dia.: 1600mm
Max. turning dia.: 1600mm
Max. turning height: 1250mm
Table dia.: 1250mm
Spindle speed: 3-300rpm
ATC: 16 positions
Live Tool Spindle
C axis

VL-160CM



Max. swing dia.: 2000mm
Max. turning dia.: 2000mm
Max. turning height: 1170 mm
Table dia.: 1600mm
Spindle speed: 3-250rpm
ATC: 16 positions
Live Tool Spindle
C axis

VL-200CM



Max. swing dia.: 2500mm
Max. turning dia.: 2500mm
Max. turning height: 1600mm
Table dia.: 2000mm
Spindle speed: 5-200rpm
ATC: 16 positions
Live Tool Spindle
C axis

VL-250CM



Max. swing dia.: 3000mm
Max. turning dia.: 2970mm
Max. turning height: 1600mm
Table dia.: 2500mm
Spindle speed: 5-160rpm
ATC: 16 positions
Live Tool Spindle
C axis

HL-32AT/MT



Max. turning dia.: 400mm
Max. cutting length: 230mm
Chuck dia.: 10 inch
Spindle bearing dia.: 120mm
Spindle speed: 25-3500rpm
Turret: 10T+10T

VL-100A



Max. swing dia.: 1320mm
Max. turning dia.: 1100mm
Max. turning height: 925mm
Chuck dia.: 40 inch
Spindle bearing dia.: 200mm
Spindle speed: 5-850rpm
Turret: H12

HONOR SEIKI Co., Ltd.

Head office & Factory

No.6 ,Sec.2 ,Chung-Shan Rd, Hu-nei Dist.,
Kaohsiung City, Taiwan.

TEL: +886 7 975 9888

FAX: +886 7 975 9999

E-MAIL: honor@honorseiki.com.tw

<http://www.honorseiki.com.tw>

Agent: